



For messages too important to miss

DM-E 65"/75" commercial LED LCD displays

Use them in conference rooms to collaborate at a larger, sharper level. Employ them at retail for lifelike, life-size images. Anywhere reliable 24/7 operation is mandatory, Samsung delivers. The DM-E Series displays incorporate innovative Samsung cooling technologies, for continuous operation and peace of mind. Images and text will always be sharp, clear and precise, with Full HD 1920 x 1080 resolution and 5000:1 contrast ratio (4000:1 on 65" model). Lightweight designs ensure installation ease, and an optional touch overlay can enable up to 10 simultaneous touch points for a greater level of interactivity. It's around-the-clock impact and reliability.

CONTACT US:

1-866-SAM4BIZ
samsung.com/business
samsung.com/b2bdigitalsignage

FOLLOW US:

youtube.com/samsungbizusa
 @SamsungBizUSA

Key features



Reliable 24/7 continuous operation

With innovative cooling technologies, Samsung DM-E Series commercial displays are designed from the chassis up to deliver the highest quality images with exceptional reliability, even during 24/7 continuous operation.



Enhanced System-on-Chip performance with quad-core CPU

Powered by a System-on-Chip semiconductor and 1GHz quad-core CPU, and featuring 8GB of storage, Samsung's SMART Signage Platform reduces TCO for digital signage deployments, providing savings in hardware, installation and operating costs.



Built-In Wi-Fi

Enjoy the advantages of expanded connectivity to mobile devices and simple mirroring of content on a tablet to the display.



MagicInfo S3 digital signage software

The software allows you to create playlists, set playback schedules and publish content directly to the display. Most traditional file formats are supported, including RSS feed and live web pages.



Ultra-slim chassis

The thin chassis (2.2" on DM65E and 2.3" on DM75E) look streamlined, help simplify installation, and also meet ADA compliance requirements.



Slim-direct LED backlight

The slim-direct-lit displays of the DM-E Series feature 1920 x 1080 Full HD resolution with 450 nits brightness and 5000:1 contrast ratio (4000:1 on DM65E) for sharp, detail-rich images and crisp, easily legible type.



Optional touch overlay with PC-less touch support

Add an optional IR touch overlay accessory to enable up to 10 simultaneous touch points. PC-less touch support means you only need to add the touch overlay accessory to enable touch, and no PC or setback box is required.

Samsung DM-E 65"/75" commercial LED LCD displays



		DM65E	DM75E	
Display	Screen Size	65"	75"	
	Panel Technology	60Hz Slim D-LED BLU	60Hz Slim D-LED BLU	
	Resolution	1920x1080 (16:9)	1920x1080 (16:9)	
	Brightness	450 nits	450 nits	
	Contrast Ratio	4000:1	5000:1	
	Viewing Angle (Horizontal/Vertical)	178° / 178°	178° / 178°	
	Orientation	Landscape / Portrait	Landscape / Portrait	
	Response Time (G-to-G)	6.5ms	4ms	
Connectivity	Input	Analog D-SUB, DVI-D (HDMI Common), DisplayPort 1.2, HDMI1, HDMI2 (thru DVI-D Input, Adapter Not Included)	Component (CVBS Common) Stereo Mini Jack, USB 2.0 x 1	
	Output	DisplayPort 1.2 (Loop-Out), Stereo Mini Jack	DisplayPort 1.2 (Loop-Out), Stereo Mini Jack	
	External Control	RS232C (In/Out) thru Stereo Jack, RJ45	RS232C (In/Out) thru Stereo Jack, RJ45	
	External Sensor	IR, Ambient Light	IR, Ambient Light	
Sound	Speaker Type	Built in Speaker (10W + 10W)	Built in Speaker (10W + 10W)	
Power	Power Supply	AC 100 - 240 V~ (+/- 10 %), 50/60 Hz		
	Power Consumption (Typical/Max)	110W / 264W	110W / 308W	
	Power Consumption (Standby)	< 0.5W	< 0.5W	
Environmental Conditions	Operating Temperature	0°C - 40°C	0°C - 40°C	
	Operating Humidity	10%~80%	10%~80%	
Features	Slim and Light LFD with Built-in MagicInfo Player S3		Slim and Light LFD with Built-in MagicInfo Player S3	
	Special	Hardware	Super Clear Coating, Temperature Sensor, Video Wall (15x15), Portrait Mode, Clock Battery (168hrs Clock Keeping), Built in Speaker (10W x 2), WiFi Module Embedded, SD Card Slot	
		Software	Magic Clone (to USB), Auto Source Switching & Recovery, RS232C/RJ45 MDC, Plug and Play (DDC2B), PIP/PEP, Image Rotation, 1 Button Lock, DP 1.2 Digital Display Chain (HDCP Support), Built-in MagicInfo S3, Firmware Update by Network, LFD New Home Screen, PC-Less Videowall, Predefined Template for Vertical Usage, Multi Channel, Mobile Control, Event Schedule, Backup Player, PC-less Touch, MagicPresenter	
	Tuner	L1 (I/D) : 32KB / 32KB L2 (Unified) : 1MB	L1 (I/D) : 32KB / 32KB L2 (Unified) : 1MB	
	SMART Signage Platform Compliant	Yes	Yes	
	Internal Media Player	Cortex-A9 1GHz Quad Core, 1.5GB DDR3, 8GB Storage, USB 2.0, Samsung Proprietary OS (VDLinux)		
	VESA Standard Wall Mount Interface	400 x 400mm	400 x 400mm	
	24/7 Operation	Yes	Yes	
	Dimensions	Product Dimensions (without stand)	57.8" x 33.4" x 2.2"	66.0" x 37.8" x 2.3"
		Packaging Dimensions	63.0" x 38.6" x 8.5"	71.3" x 42.7" x 9.8"
Bezel Width		18.0mm (Top, Left), 23.5mm (Right, Bottom)	12.0mm (Top, Left), 17.3mm (Right, Bottom)	
Weight	Product Weight	60.4 lbs.	75.2 lbs.	
	Shipping Weight	78 lbs.	97.2 lbs.	
Service	Standard Warranty	3 Years On-Site (Parts / Labor / Backlight)		
Accessories	Included	Quick Setup Guide, Regulatory Guide, Warranty Card, D-Sub Cable, Power Cord, Remote Controller, Batteries, RS232C (IN) Adapter, Cover-Jack		
	Optional Mount	WMN4675MD, WMN4277SD, WMN6575SD, CML450D (Ceiling Mount)	WMN4675MD, WMN4277SD, WMN6575SD, CML450D (Ceiling Mount)	
	Optional Stand	STN-L6500E	STN-L7585F (New Stand)	
	External Media Player	SBB (Optional), PIM (Optional)	SBB (Optional), PIM (Optional)	
	Optional Touch Overlay	TE65ECD	CY-TD75LDAF	
Green Management	Emission Standard	EMC	EMC	
	ENERGY STAR® 6.0 Compliant	N/A	N/A	
	RoHS Compliant	Yes	Yes	
	Packaging Recyclability	Packing Materials Recyclable	Packing Materials Recyclable	

CONNECTIVITY

1. RS232C In
2. RS232C Out
3. IR/Ambient Sensor In
4. Audio In
5. Audio Out
6. SD Card Slot
7. USB
8. DVI In
9. DisplayPort In
10. HDMI In
11. VGA In
12. DisplayPort Out
13. Antenna In
14. AV In
15. IR Out
16. RJ45 In



Learn more samsung.com/business or samsung.com/b2bdigitalsignage
Product support 1-800-SAMSUNG 1-866-SAM4BIZ
Follow us [youtube.com/samsungbizusa](https://www.youtube.com/samsungbizusa) [@SamsungBizUSA](https://twitter.com/SamsungBizUSA)

SAMSUNG
BUSINESS

Samsung Electronics has been named 2015 ENERGY STAR Partner of the Year in the product manufacturing category by the U.S. Environmental Protection Agency (EPA).

©2015 Samsung Electronics America, Inc. Samsung is a registered mark of Samsung Electronics Corp., Ltd. Specifications and design are subject to change without notice. Non-metric weights and measurements are approximate. All brand, product, service names and logos are trademarks and or registered trademarks of their respective manufacturers and companies. See samsung.com for detailed information. Printed in USA. LFD-DMESERIESDSHT-AUG15T

